



CHAINE FILANTE CF

PROFESSIONAL-QUALITY CHAINSAW CHAIN OIL

APPLICATIONS

Sticky oils for lubricating the chains of chainsaws.

- + **CHAINE FILANTE 75 F** is a professional-grade product for use in all seasons.
- + **CHAINE FILANTE 95 F** is professional quality for sawmills and foresters
- + **CHAINE FILANTE 125 F** is a professional-grade product that is particularly recommended in summer.

ADVANTAGES

- Smooth oils are lubricants enhanced with polymers to make the oil film sticky on the chain and its guide.
- **CHAINE FILANTE 75 F** has excellent fluidity in winter and good adhesion to the chain and its guide when used in periods of hot weather.
- **CHAINE FILANTE 95 F** has a viscosity that means it can be used all year round and increased adhesion, offering better adhesion to the chain guide.
- **CHAINE FILANTE 125 F** has a very thick quality for very hot periods and intensive use. It reduces oil consumption while providing perfect protection for the chain and its guide. It also reduces oil splashes.

PERFORMANCE

The **CHAINE FILANTE** range complies with the requirements of:

MAC CULLOCH, HOMELITE, HUSQVARNA, STIHL, etc.

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	AVERAGE VALUES		
			75 F	95 F	125 F
Professional quality	-	-	75 F	95 F	125 F
Density at 15°C	kg/m ³	NF T 60-101	868.3	863	872.2
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	130	150	220
Flash point	°C	NF T 60-118	253.7	244	275.6
Pour point	°C	NF T 60-105	-9	-12	-9

The average characteristics are provided for information purposes

HEALTH, SAFETY AND ENVIRONMENT

Disposal must comply with applicable regulations pertaining to the disposal of used oils.

Store in a location sheltered from weather

Our technical department is available to provide advice if needed.