



MATIC D

FLUID FOR AUTOMATIC GEAR-BOXES

TRANSMISSION RANGE
AUTOMATIC GEAR-BOXES
MINERAL

Mineral

Semi-synthetic

100% synthetic

MANUFACTURING STANDARDS
GM DEXRON®-IID
MB 236.7
VOITH TURBO H55.6335
ZF TE-ML 04D, 11A, 14A

Oxidation resistance



Anti-wear level



APPLICATIONS

MATIC D is used for all automatic transmissions and hydraulic circuits for which a DEXRON®-II D fluid is recommended by the manufacturer.

- Automatic gearboxes
- Couplers, converters
- Power steering
- Hydrostatic transmissions

BENEFITS

- Reinforced anti-wear power
- Good friction properties
- High anti-oxidant power
- Neutral to seals, ferrous and non-ferrous metals

PERFORMANCE

APPROVALS (1)

VOITH TURBO H55.6335 (G607)
ZF TE-ML 04D, 11A, 14A (ZF001071)

PERFORMANCE LEVELS

ALLISON C3/C4
CATERPILLAR TO-2
FORD M2C 138 CJ
GM DEXRON®-IID
IVECO 18-1807 classe AG2
MB 236.7
ZF TE-ML 03D, 05L, 17C

(1) Approval certificates available on request

OPAL
MM
OPAL
MM



CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
ISO grade	-	-	32 - 46
Colour	-	Visual	red
Density at 15°C	kg/m ³	NF T 60101	874
Kinematic viscosity at 40°C	mm ² /s	NF T 60100	39.7
Kinematic viscosity at 100°C	mm ² /s	NF T 60100	7.35
Viscosity index	-	NF T 60136	152
Brookfield viscosity at -40°C	mPa.s	NF T 60152	44 500
Pour point	°C	NF T 60105	-42
Flash point	°C	NF T 60118	194

The above data are provided on an indicative basis only..

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

Must be stored away from bad weather conditions.

For further details, our Technical Department is available to assist you.